



Engineered to elevate efficiency and comfort
..... to the next level!!

WEFC SERIES

Floor Ceiling Fan Coil Units

235-1,200 CFM (400-2,040 m³/h)

Cooling Capacity: 10,000-33,100 Btuh (2.9-9.7 kW)

Heating Capacity: 18,300-54,250 Btuh (5.4-15.9 kW)

Product Features (Standard)

- ✓ Cooling & Heating.
- ✓ Auto Clean Function.
- ✓ Inner Groove Cooper Tubes.
- ✓ Compact Design.
- ✓ Multi Fan with 3 Speeds.
- ✓ Wireless Remote Controller.
- ✓ Easy Connect Threaded Brass Connections.
- ✓ Self Diagnosis.
- ✓ Whisper Quiet Design.
- ✓ Anti-Cold Function.
- ✓ Washable Filter.
- ✓ Microcomputer Control.

Product Features (Optional)

- ✓ Wired Remote Controller (WCA-CC308).
- ✓ 3 Way Electronic Valve, 3/4 (WECA-3V340A).
- ✓ Copper Fins.



Standard Wireless Controller



Optional Wired Controller



A Product of
OMEGA
Environmental
Technologies LLC.

ISO 14001 ISO 9001



Engineered to elevate efficiency and comfort
..... to the next level!!

WEFC SERIES

Floor Ceiling Fan Coil Units

235-1,200 CFM (400-2,040 m³/h)

Cooling Capacity: 10,000-33,100 Btuh (2.9-9.7 kW)

Heating Capacity: 18,300-54,250 Btuh (5.4-15.9 kW)

WATER FLOOR CEILING	MODEL NO.	WEFC	002C2	003C2	004C2	005C2	006C2	007C2	010C2	012C2	
			W-RWTN034	W-RWTN051	W-RWTN068	W-RWTN085	W-RWTN102	W-RWTN136	W-RWTN170	W-RWTN204	
	Air Flow Volume (Hi)	CFM (m ³ /hr)	235 (400)	300 (510)	400 (680)	485 (820)	600 (1020)	700 (1190)	1000 (1700)	1200 (2040)	
	Cooling Capacity	Btuh (kw)	10,000 (2.9)	11,325 (3.3)	14,675 (4.3)	17,640 (5.2)	19,380 (5.7)	24,055 (7.1)	30,705 (9.0)	33,100 (9.7)	
	Heating Capacity	Btuh (kw)	18,300 (5.4)	19,650 (5.8)	23,715 (7.0)	27,640 (8.1)	31,390 (9.2)	36,165 (10.6)	49,475 (14.5)	54,250 (15.9)	
	Water Flow Rate	GPM (L/S)	2.21 (0.14)	2.53 (0.16)	3.32 (0.21)	3.96 (0.25)	4.12 (0.26)	5.07 (0.32)	6.81 (0.43)	7.29 (0.46)	
	Water Pressure drop	ft-wtr (kPa)	3.34 (10.0)	4.03 (12.0)	6.02 (18.0)	10.04 (30.0)	16.72 (50.0)	18.40 (55.0)	18.40 (55.0)	18.40 (55.0)	
	Coil Type		Aluminum fin - Copper tube								
	Coil face Area	Sqft	2.36	2.36	2.36	2.36	5.50	5.50	7.85	7.85	
	Coil face Velocity	f/m (m/s)	98.4 (0.50)	125.9 (0.64)	167.3 (0.85)	202.8 (1.03)	108.3 (0.55)	125.9 (0.64)	125.9 (0.64)	151.6 (0.77)	
Electrical	Voltage	208 - 230 /1/60 Hz									
	FLA	0.22	0.24	0.33	0.38	0.48	0.50	0.79	1.03		
	Input (W)	47	49	69	81	99	103	165	215		
Fan Motor	Type	PSC - Permanent Split Capacitor Motor									
	Speed	3-Speed									
	Type	Centrifugal									
	Noise L. Hi (db)	41	41	46	49	51	51	48	50		
Air Filter		Cleanable Cartridge Type									
Water Connections In & Out inches (mm)		3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)		
Drain Connections Threaded inches (mm)		3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)		
Dimensions inches (mm)	Height	9 1/3 (238)	9 1/3 (238)	9 1/3 (238)	9 1/3 (238)	7 1/2 (188)	7 1/2 (188)	9 1/3 (238)	9 1/3 (238)		
	Width	32 7/8 (834)	32 7/8 (834)	32 7/8 (834)	32 7/8 (834)	51 1/8 (1300)	51 1/8 (1300)	62 1/2 (1590)	62 1/2 (1590)		
	Depth	27 1/3 (694)	27 1/3 (694)	27 1/3 (694)	27 1/3 (694)	23 5/8 (600)	23 5/8 (600)	7 7/8 (695)	7 7/8 (695)		
Net Weight Lbs (kgs)		57.3 (26)	57.3 (26)	57.3 (26)	57.3 (26)	75.0 (34)	75.0 (34)	108.1 (49)	108.1 (49)		

Notes:

- Nominal cooling capacities are based in Floor Ceiling Water Fan Coil, air entering conditions DB : 27 ° C (80° F) WB : 19 ° C (66.2° F) entering chilled water conditions : 7 ° C (44.6° F) leaving chilled water conditions : 12 ° C (53.6° F) at High Speed Fan , 220/1/60Hz.
- Sound Power level will be according to ISO 5151, Sound Pressure calculated at 1m of distance.
- For details of model number nomenclature, please refer to publication OMGNM-0215.



ENVIRONMENTAL TECHNOLOGIES LLC.

17702 Mitchell North, #101
Irvine, CA 92614, USA

Tel: 714 796 2830
Fax: 714 966 1649

info@oetusa.com
www.omegaenvironmentaltechnologies.com



AIR CONDITIONING Showroom & Technology Center

11380 Interchange Circle North
Miramar, FL 33025 . USA

Tel: 305 731 2140, 888 840 7550
Fax: 954 212 8280

info@otecus.com
www.otecus.com

ISO 14001 ISO 9001