

CW120-PR3(W,B) Programmable Fan Coil Thermostat

CETO[®]
CONTROLS

- 110/220 Volt Switchable
- Touch Screen Controls
- High, Medium, Low, and Auto Fan Settings
- 3 Speed Fan Operation
- Sleep and Timer ON/OFF Function
- Auto Restart Function
- Delayed Valve Start Option
- Valve Position Display
- Fahrenheit or Celsius Temperature Display
- Built in IR Receiver (Optional Remote Controller)
- Compatible with Universal Motion Remote (UMR-903)
- Controls 2 or 3 Wired & Cool/Heat Valve
- White Backlight with Automatic Light Adjustment
- Ambient and Set Temperature Display
- Dimensions: 4 5/8" x 3 3/8" x 5/8" (118 x 86 x 16 mm)



Other CETO Products

CSV23-FT050B Zone Valve

Stainless Steel Spring Return
Totally Enclosed Uni-Directional Synchronous Motor
Two Position
Brass Body
Normally Closed Actuators
Pop-top Connection
Manual Override
110/220V – 50/60Hz




UMR-904 Universal Motion Remote

Selectable for over 6,000 A/C brands
Requires 3x AAA Batteries
Occupancy Sensor
Temperature & Humidity Display
No Wiring Required
Fahrenheit or Celsius Temperature Conversion
Compatible with Wireless Systems with Receiver
Dimensions: 4 1/2" x 3" x 7/8" (112 x 76 x 22 mm)



CX024-SP1 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
5+2 Weekly Programmable
Fahrenheit or Celsius Temperature
Auto Function.
One Stage Cool and One Stage Heat Operation
5 Minutes Compressor Delay Protection
Adjustable Cooling Cycle Rate
Dimensions: 4 5/8" x 3 3/8" x 1" (118 x 85 x 25 mm)



CX024-DP2 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
5+2 Touch Screen Programmable
6.8 Sq. In. Display
Adjustable Cooling Cycle Rate
AUTO Function
Two Stage Cool and Two Stage Heat Operation
5 Minutes Compressor Delay Protection
Dimensions: 4 5/8" x 3 1/2" x 1 1/2" (118 x 88 x 30 mm)



CX024-PR2 Programmable WIFI Thermostat

24V Hard Wired
5+2 Touch Screen Programmable
7 Sq. in. Touch Screen Display
Adjustable Cooling Cycle Rate
AUTO Function
5 Minutes Compressor Delay Protection
Two Stage Cool and Two Stage Heat Operation
Dimensions: 4 5/8" x 3 3/8" x 1" (118 x 88 x 27 mm)



UAR-409 Universal A/C Wireless Remote

4000 Codes in 1 Controller
Codes Inputting
Timer On/Off functionality and Digital key Input Clock Function
Fahrenheit or Celsius Temperature Conversion Auto Search Function
Selectable for over 6,000 A/C brands
Dimensions: 4 1/2" x 3" x 7/8" (112 x 76 x 22 mm)

