



CX024-SP1 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
 5+2 Weekly Programmable
 Fan ON
 Auto Function.
 One Stage Cool and One Stage Heat Operation
 5 Minutes Compressor Delay Protection

Adjustable Cooling Cycle Rate
 Fahrenheit or Celsius Temperature
 Display Low Battery Indicator
 Filter Usage Counter
 Backlight On/Off Setting
 Dimensions:
 4 5/8" x 3 3/8" x 1" (118 x 85 x 25 mm)



CX024-DP2 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
 5+2 Touch Screen Programmable
 6.8 Sq. In. Display
 Fan ON
 AUTO Function
 Two Stage Cool and Two Stage Heat Operation
 5 Minutes Compressor Delay Protection

Adjustable Cooling Cycle Rate
 Fahrenheit or Celsius Temperature
 Display Low Battery Indicator
 Backlight On/Off Setting
 Dimensions:
 4 5/8" x 3 1/2" x 1 1/2" (118 x 88 x 30 mm)



CW120-PR3 Programmable Fan Coil Thermostat

110/220 Volt Switchable
 Touch Screen Controls
 High, Medium, Low, and Auto Fan Settings
 3 Speed Fan Operation
 Sleep and Timer ON/OFF Function
 Auto Restart Function
 Delayed Valve Start Option
 Valve Position Display
 Fahrenheit or Celsius Temperature Display

Built in IR Receiver (Optional Remote Controller)
 Compatible with Universal Motion Remote (UMR 903)
 Controls 2 or 3 Wired & Cool/Heat Valve
 White Backlight with Automatic Light
 Adjustment Ambient and Set Temperature
 Display Dimensions:
 4 5/8" x 3 3/8" x 5/8" 118 x 86 x 16 mm



CX024-PR2 Programmable WIFI Thermostat 24V

Hard Wired
 5+2 Touch Screen Programmable
 7 Sq. in. Touch Screen Display
 Fan ON
 AUTO Function
 Compatible with Universal Motion Remote (UMR 903)
 Two Stage Cool and Two Stage Heat Operation

Two Stage Cool and Two Stage Heat Operation
 5 Minutes Compressor Delay Protection
 (Selectable ON/OFF)
 Adjustable Cooling Cycle Rate
 Fahrenheit or Celsius Temperature Display
 Backlight On/Off Setting
 Dimensions:
 4 5/8" x 3 3/8" x 1" (118 x 88 x 27 mm)



UAR-409 Universal A/C Wireless Remote

4000 Codes in 1 Controller
 Codes Inputting
 Timer On/Off functionality and Digital key Input
 Clock Function
 Fahrenheit or Celsius Temperature Conversion
 Auto Search Function

Functions with Fixed-Frequency and Inverter Systems
 Compatible with 98% of Air Conditioners Worldwide
 Battery Powered with Two AAA (VM-4,R03)
 Controllable Distance of more than 8 meters
 Power Supply Voltage of DC3V
 Dimensions:
 4 5/8" x 1 3/4" x 5/8" (123 x 44 x 22 mm)



UMR-904 Universal Motion Remote

Programmable
 Requires 3x AAA Batteries
 Occupancy Sensor
 Temperature & Humidity Display
 No Wiring Required
 Fahrenheit or Celsius Temperature Conversion

24 Hour Clock
 Compatible with all Wireless Control Systems with Receiver
 Delayed Stop Mode
 Selectable for over 6,000 A/C brands
 Compatible with Fan Coil Water Thermostat (CW120 PN3)
 Dimensions:
 4 1/2" x 3" x 7/8" (112 x 76 x 22 mm)



CETO[®] CONTROLS



High Wall



Programmable Fan
Coil Thermostat



PTAC



Ceiling Cassette



Ducted Fan Coil



Floor/Ceiling



Schools



Offices



Apartments



AIRBNB / Hotel Room



An **OMEGA** Company