







- No Expensive Wiring
- No Electric Bill
- Easy to Install
- Dusk to Dawn
- Charges During the Day
- · Lights Up at Night





- Built-in Motion Sensor For 100% Brightness
- Infrared Remote Control Adjusts Brightness: 30% & 100%

SAVES ENERGY INSTANT LIGHT ANYWHERE ANYTIME



Available In 3 Sizes







60 W



90 W













Ideal Applications

- Building Exterior Lighting
- Unlit Driveways
- Walkways
- Backyards
- Patio





30 Watts





FACTS

- Subtle glow for cozy ambiances, perfect for garden pathways or patios.
- Soft luminescence ideal for intimate gatherings.
- Energy-efficient for low-intensity lighting needs.

60 Watts

:ACTS

- Suitable for medium-sized spaces like backyards and outdoor seating.
- Provides comfortable illumination for both residential and commercial uses.
- Effective visibility for commercial signage.





90 Watts



)

- Ideal for lighting expansive spaces like parking lots and sports courts.
- Enhances security with strong illumination.
- Energy-efficient solution for high visibility needs.

MODEL	CPSL-A030-A2	CPSL-A060-A2	CPSL-A090-A2
Watt	30	60	90
Led Qty	30 Pcs Double Cover	60 Pcs Double Cover	90 Pcs Double Cover
Solar Panel Voltage	3.2 V		
Type of Battery	LIFE PO4		
Battery Capacity (Ah)	5	10	15
Battery Life (Hours)	15000		
Sensor Beam Angle (Deg)	120		
Lighting Area (m^2)	40	50	60
Lumens	40000	60000	90000
Installation Height (m)	3-4 Meters	5-6 Meters	6-7 Meters
Working Temperature (C)	-15 C +60C		
Motion Sensor Distance	10-12 Meters		
Protection Class	IP 65 - Class III		
Unit Dimension (mm)	186x375x49	210x467x49	225x625x49
Packing Dimension (mm)	200x390x60	225x480x60	240x640x60



Showroom & Technology Center 11380 Interchange Circle North Miramar, Florida, 33025, USA Tel: 888-840-7550 Fax: 954-212-8290 info@ceto-controls.com www.ceto-controls.com

