

# OMEGA TECHNOLOGY

Engineered to elevate efficiency and comfort .....  
..... to the next level!

## WPCH SERIES WATER COOLED PACKAGE HORIZONTAL TYPE

R410A Refrigerant

Cooling Nominal: 2 - 5 Tons (7.0-17.5 kW)

### Product Features

- ✓ 24V. Control Circuit.
- ✓ High efficiency scroll compressor.
- ✓ Multi-speed blower motor.
- ✓ TXV metering device.
- ✓ Galvanized prepainted steel casing.
- ✓ Compact Design.
- ✓ Easy Maintenance.
- ✓ Compact condenser with high efficiency.
- ✓ Reduced volume of water to be circulated.
- ✓ Reduced condenser water pipe sizes and pumps.
- ✓ Efficient Liquid Refrigerant Sub Cooling.
- ✓ Drainable water tubes.
- ✓ Low water side pressure drops.
- ✓ Low operating cost.
- ✓ Factory mounted hanger brackets.
- ✓ Removable panels for service access.
- ✓ High and low pressure Service Port.
- ✓ Quiet Operation.
- ✓ Heat exchanger tested at 660psi.



OMEGA

OTEC  
AIR CONDITIONING

A Product of  
**OMEGA**  
Environmental  
Technologies LLC.

ISO 14001 ISO 9001





Engineered to elevate efficiency and comfort .....  
 ..... to the next level!

**WPCH SERIES**  
**WATER COOLED PACKAGE**  
**HORIZONTAL TYPE**  
**R410A Refrigerant**  
 Cooling Nominal: 2 - 5 Tons (7.0-17.5 kW)

**WATER SOURCE**

MODEL NO.	WPCH	024C2A -TC1070	036C2A -TC1105	048C2A -TC1140	060C2A -TC1175
Total Capacity	Btuh (kw)	24,000 (7.0)	36,000 (10.5)	48,000 (14.0)	60,000 (17.5)
Sensible Capacity	Btuh (kw)	16,560 (4.9)	27,360 (8.0)	36,480 (10.7)	43,800 (12.8)
Air Flow @ esp 0.4 in (100pa)	CFM (m³/hr)	800 (1360)	1200 (2040)	1600 (2720)	2000 (3400)
Coil Type	Aluminum fin - Copper tube 4 row coil.				
Coil face Area	Sqft (Sqm)	1.75 (0.16)	2.89 (0.27)	3.88 (0.36)	3.88 (0.36)
Coil face Velocity	f/m (m/s)	457 (2.32)	415 (2.10)	412 (2.09)	412 (2.09)
Condenser Type	Shell & Tube				
Water Flow Rate	GPM (L/S)	4 (0.25)	6 (0.38)	8 (0.61)	10 (0.63)
Water Pressure drop	ft-wg (kPa)	9.2 (27.5)	3.5 (10.3)	10.4 (31.0)	21.9 (65.5)
Fan Motor	Type	PSC - Permanent Split Capacitor Motor			
	HP	1/4	1/3	1/2	3/4
	Speed	3-Speed			
	Type	Centrifugal			
	Fan Qty	1	1	1	1
	Blower Size (in)	9 x 7	10 x 8	10 x 10	10 x 10
Compressor	Indoor Fan (FLA)	1.5	1.9	2.9	4.0
	Type	Scroll			
	RLA (208/230)	15.0 / 13.5	18.6 / 16.7	23.9 / 21.4	29.3 / 26.3
Electrical	LRA	58.3	79.0	135.0	134.0
	Voltage	208 - 230/1/60 Hz			
	Range	min 198 ~ max 242			
	Min. Circuit Amps (MCA)	20.3	25.2	32.8	40.6
Refrigerant R-410A (oz./kg)	Max. Fuse Amps (MOCP)	35	40	50	60
		39 / 1.1	48 / 1.4	73 / 2.1	78 / 2.2
Water Connections M.P.T - In/Out in. (mm)		3/4 (19.05)	3/4 (19.05)	1 (25.4)	1 (25.4)
Drain Connections Threaded inches (mm)		3/4 (19.05)			
Filter Dimension		18 x 16.4	18 x 25	18 x 33.5	18 x 33.5
Dimensions inches (mm)	Height	19 5/8 (500)	19 5/8 (500)	19 5/8 (500)	19 5/8 (500)
	Width	35 7/8 (910)	45 1/4 (1150)	51 1/4 (1300)	51 1/4 (1300)
	Depth	21 1/4 (540)	25 5/8 (650)	25 5/8 (650)	25 5/8 (650)
Net Weight Lbs (kgs)		220 (100)	264 (120)	279 (127)	281 (128)

**Notes:** 1. Nominal capacities are based on air entering the evaporator section at 80/67°F (27/19°C), DB/WB indoor & 85°F (29°C) water temperature entering condenser with indoor fan operating at high airflow setting.  
 2. For details of model number nomenclature, please refer to publication OMGNM-0118.

**OMEGA**  
 ENVIRONMENTAL  
 TECHNOLOGIES LLC.  
 17702 Mitchell North, #101  
 Irvine, CA 92614, USA  
 Tel: 714 795 2830  
 Fax: 714 966 1649  
 info@oetusa.com  
 www.omegaaenvironmentaltechnologies.com

**OTEC**  
 AIR CONDITIONING  
 Showroom & Technology Center  
 11380 Interchange Circle North  
 Miramar, FL 33025 . USA  
 Tel: 305 731 2140, 888 840 7550  
 Fax: 954 212 8280  
 info@otecus.com  
 www.otecus.com

**ISO 14001 ISO 9001**