

OMEGA VRF TECHNOLOGY

INVERTER
TECHNOLOGY
EXPERT

Engineered to elevate efficiency and comfort
..... to the next level!

VMEP SERIES Full DC Modular VRF Outdoor Unit (220~240V/3 Phase) 3D Inverter Cooling Only

Cooling Capacity Min~Max Single Module: 38,215~305,375 BTU/h (11.2~89.5 kW)

Product Features

- ✓ DC Inverter Technologies.
- ✓ Up to 50 Indoor Units Could be Connected per System.
- ✓ Intelligent Temperature Control Technology.
- ✓ Oil Balance Control Technology.
- ✓ Network Connection Technology.
- ✓ Factory Tested up to 50°C/122°F Ambient.
- ✓ Ultra Long Piping Run up to 3280 ft.
- ✓ Automatic Address Setting.
- ✓ Anticorrosive Hydrophilic Coated Fins.
- ✓ Modules Rotation Operating to Improve Lifetime.

Outdoor Unit Features

- ✓ Low Noise Design with Sensorless Inverter DC Fan Motor.
- ✓ Advance Torque Control Technology.
- ✓ Multi Electronic Expansion Valves Control.
- ✓ High Efficiency Digital PFC Control.
- ✓ Wider Operation Condition Range.
- ✓ Compressor Oil Storage Technology.
- ✓ Two Stage Oil Separation Technology.
- ✓ Automatic Fault Detection.



008 - 016 HP



018 - 022 HP



Branch Pipe Kit



024 - 028 HP

OMEGA



ISO 14001 ISO 9001

OTEC
AIR CONDITIONING

A Product of
OMEGA
Environmental
Technologies LLC.

OMEGA VRF TECHNOLOGY

INVERTER TECHNOLOGY EXPERT

Engineered to elevate efficiency and comfort
..... to the next level!

VMEP SERIES Full DC Modular VRF Outdoor Unit (220~240V/3 Phase) 3D Inverter Cooling Only

Cooling Capacity Min~Max Single Module: 38,215~305,375 BTU/h (11.2~89.5 kW)

MODULAR VRF Outdoor Unit

MODEL NO.	VMEP	007N4A -D13V224	009N4A -D16V280	010N4A -D20V335	012N4A -D23V400	014N4A -D26V450	016N4A -D29V500	018N4A -D33V560	020N4A -D36V615	022N4A -D39V670	024N4A -D43V730	026N4A -D46V785	028N4A -D50V850
System Cooling Indoor Unit Ratio @ 100% BTU/h (kW)		76,430 (22.4)	95,540 (28.0)	114,305 (33.5)	136,485 (40.0)	153,545 (45.0)	170,610 (50.0)	190,080 (56.0)	209,845 (61.5)	228,615 (67.0)	249,080 (73.0)	267,840 (78.5)	290,020 (85.0)
EER @ 100% BTU/h / W (W/W)		14.6 (4.27)	13.4 (3.94)	12.8 (3.76)	13.2 (3.88)	12.8 (3.75)	12.5 (3.65)	11.6 (3.39)	10.7 (3.13)	10.4 (3.33)	11.0 (3.29)	10.8 (3.25)	10.5 (3.09)
System Cooling Indoor Unit Ratio @ 50% BTU/h (kW)		38,215 (11.2)	47,770 (14.0)	57,325 (16.8)	68,245 (20.0)	76,775 (22.5)	85,305 (25.0)	95,540 (28.0)	105,095 (30.8)	114,310 (33.5)	124,540 (36.5)	134,090 (39.3)	145,010 (42.5)
System Cooling Indoor Unit Ratio @ 70% BTU/h (kW)		53,570 (15.7)	66,880 (19.6)	80,185 (23.5)	95,540 (28.0)	107,480 (31.5)	119,425 (35.0)	133,755 (39.2)	147,065 (43.1)	160,030 (46.9)	174,350 (51.1)	187,660 (55.0)	203,015 (59.5)
System Cooling Indoor Unit Ratio @ 130% BTU/h (kW)		80,865 (23.7)	100,995 (29.6)	120,445 (35.3)	144,330 (42.3)	161,730 (47.4)	180,495 (52.9)	201,990 (59.2)	221,100 (64.8)	241,570 (70.8)	263,405 (77.2)	282,170 (82.7)	305,375 (89.5)
Total Number of Outdoor Modules Connectable		3											
Max. Cooling Capacity 3 modules @ 100% BTU/h (kW)		870,060 (255)											
Coil Type		Grooved Cooper Tubes - Hydrophilic Aluminum Fin											
Fan	Type	Axial Fan											
	Qty	1	1	1	1	1	2	2	2	2	2	2	2
	Motor (FLA) each	3.8	3.8	4.4	5.8	5.8	8	8.5	8.5	9.2	9.2	10	10
	R.P.M. Range (Min~Max)	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950	0 ~ 950
	Air Flow CFM (m³/hr) (Hi)	6,120 (10,400)	6,120 (10,400)	6,360 (10,800)	6,830 (11,600)	6,830 (11,600)	7,060 (12,000)	7,180 (12,200)	7,180 (12,200)	11,540 (19,600)	11,540 (19,600)	12,130 (20,600)	12,130 (20,600)
	Ext. Sta. Pressure. In.W.G. (Pa)	0.08 (20)											
Noise Level Hi (dbA)	57	58	60	60	61	62	63	63	64	64	64	64	
Electrical	Voltage-Phase-Frequency	220/240V - 3Ph - N/A (3D)											
	Rated Input / Cooling (kW)	5.25	7.10	8.90	10.3	12.0	13.7	16.5	19.7	20.1	22.2	24.2	27.5
	Rated Current / Cooling (A)	23.9	32.3	40.5	46.8	54.5	62.3	75	89.3	91.4	100.9	109.9	125.0
	Min. Circuit Amps (MCA)	42.5	42.8	43	47	47.5	85.5	86	86.5	91	91.5	92	92.5
	Max. Fuse Amps (MOCP)	50	50	50	63	63	100	100	100	100	100	100	100
Refrigerant Charge R410A (oz / kgs)		282.1 / 8.0	282.1 / 8.0	282.1 / 8.0	387.9 / 11	387.9 / 11	458.5 / 13	458.5 / 13	458.5 / 13	670.0 / 19	670.0 / 19	670.0 / 19	670.0 / 19
Refrigerant Connections inches (mm)	Type	Sweat											
	Liquid	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	5/8 (15.9)	5/8 (15.9)	5/8 (15.9)	5/8 (15.9)	5/8 (15.9)	3/4 (19.1)	3/4 (19.1)	3/4 (19.1)	3/4 (19.1)
Suction	1 (25.4)	1 (25.4)	1 1/8 (28.6)	1 1/4 (31.8)	1 1/4 (31.8)	1 1/4 (31.8)	1 1/4 (31.8)	1 1/4 (31.8)	1 1/4 (31.8)	1 3/8 (34.9)	1 3/8 (34.9)	1 3/8 (34.9)	1 3/8 (34.9)
Farthest Indoor Pipe Length Ft. (m)		655 (200)											
Maximum Total Pipe Length Ft. (m)		3280 (1000)											
Height Difference between IDU & ODU Ft. (m)		360 (110) See Note (5)											
Dimensions inches (mm)	Height	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)	63 5/8 (1615)
	Width	37 7/8 (960)	37 7/8 (960)	37 7/8 (960)	37 7/8 (960)	37 7/8 (960)	49 1/2 (1250)	49 1/2 (1250)	49 1/2 (1250)	62 3/8 (1585)	62 3/8 (1585)	62 3/8 (1585)	62 3/8 (1585)
	Depth	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)	30 1/8 (765)
Net Weight lbs (kgs)		425 (193)	425 (193)	425 (193)	441 (200)	441 (200)	653 (296)	653 (296)	653 (296)	776 (352)	776 (352)	776 (352)	776 (352)

Notes:

- Nominal capacities are based on ARI standards 210/240-89, air entering the indoor coil operating at high fan speed for 208V-230V setting.
Cooling: 80/67° F (27/19° C) DB/WB indoor & 95° F (35° C) outdoor ambient temperature.
- Refrigerant metering device is installed at the indoor unit as standard.
- Sweat fittings are provided for connecting indoor and outdoor units.
- Insulation of both liquid and suction line is required (Heat Pump Model).
- Total Height difference could reach 590 ft (180m) with ODU's installed above & below IDU's levels.
- Max Capacities per Module based on 130% Indoor Loading.
- For details of model number nomenclature, please refer to publication OMGNM-0520.

OMEGA
ENVIRONMENTAL
TECHNOLOGIES LLC.
17702 Mitchell North, #101
Irvine, CA 92614, USA
Tel: 714 795 2830
Fax: 714 966 1649
info@omegainverter.com
www.omegainverter.com



ISO 14001 ISO 9001

OTEC
AIR CONDITIONING
Showroom & Technology Center
11380 Interchange Circle North
Miramar, FL 33025, USA
Tel: 305 731 2140, 888 840 7550
Fax: 954 212 8280
info@otecus.com
www.otecus.com