

OMEGA TECHNOLOGY

Engineered to elevate efficiency and comfort
..... to the next level!

IEMP SERIES

Medium ESP Ducted Fan Coil
Inverter Air Conditioner 50 Hz

Cooling Nominal: 18,000 - 60,000 BTU/h (5.3 -16.0 kW)

Heating Nominal: 18,000 - 60,500 BTU/h (5.3 -17.7 kW)

Product Features

- ✓ Heating and Cooling System
- ✓ Ideal for Small Commercial & industrial Applications
- ✓ Auto Restart.
- ✓ Heat Pump.
- ✓ Low Voltage Start Up.
- ✓ Factory Tested.
- ✓ Discharge Heat Temperature Protection

Outdoor Unit Features

- ✓ Multiple Protection
- ✓ AC Fan Motor
- ✓ High-Efficiency Outdoor Fan
- ✓ Motor Overload Protection
- ✓ High/Low Pressure Protection
- ✓ Leakage Refrigerant Protection
- ✓ Optimized Air-Outlet Grill
- ✓ Anit Rust Metal Design
- ✓ Self Diagnostics

Indoor Unit Features

- ✓ Flexible Installation
- ✓ Sleek and Space Saving
- ✓ Multi-Position Air Intake
- ✓ Turbo Cooling Function with Multi-Speed Fan Control.
- ✓ Built in Drain Pump (Optional).
- ✓ Easy Maintenance and Cleanable Cartridge Filters.
- ✓ Dual-direction Drainage Pipe Design
- ✓ Auto-Restart
- ✓ Quiet Operation
- ✓ AC Fan Motor
- ✓ Standard Wired Controller
- ✓ Optional Wireless Controller



OMEGA



ISO 14001 ISO 9001

OTEC
AIR CONDITIONING

A Product of
OMEGA
Environmental
Technologies LLC.

Engineered to elevate efficiency and comfort
..... to the next level!

INDOOR UNIT								
MODEL NO.	IEMP	018J3A -LCG053	024J3A -LCG070	030J3A -LCG090	036J3A -LCG105	048J3A -LCG140	060J3A -LCG160	
Cooling Capacity BTU/h (kW)	Nominal	18,000 (5.3)	24,000 (7.0)	30,000 (9.0)	36,000 (10.5)	48,000 (14.0)	60,000 (16.0)	
	Minimum	6,200 (1.8)	8,550 (2.5)	10,600 (3.1)	12,550 (3.7)	16,700 (4.9)	19,100 (5.6)	
	Maximum	18,600 (5.5)	25,400 (7.5)	31,400 (9.2)	37,500 (11.0)	50,150 (14.7)	57,300 (16.8)	
Cooling - EER (W/W)		3.01	3.02	3.21	3.02	3.01	3.02	
	Nominal	19,500 (5.7)	26,000 (7.6)	32,000 (9.4)	39,400 (11.6)	52,500 (15.4)	58,000 (17.0)	
	Minimum	6,800 (2.0)	6,800 (2.7)	11,450 (3.4)	13,800 (4.1)	18,400 (5.4)	20,300 (5.9)	
Heating Capacity BTU/h (kW)	Maximum	20,400 (5.9)	27,200 (7.9)	34,100 (10.0)	41,300 (12.1)	54,950 (16.1)	63,800 (18.7)	
	Heating - COP (W/W)	3.42	3.42	3.41	3.41	3.41	3.42	
	Refrigerant Control	Electronic Expansion Valve @ Outdoor Unit						
Fan	Type	Centrifugal						
	Speed	4						
	Air Flow CFM (m3/hr) - Hi	500 (850)	650 (1100)	885 (1500)	885 (1500)	1295 (2200)	1295 (2200)	
	Noise Level (dBa) - Hi/Lo	38/35	40/36	46/40	47/40	49/42	49/42	
	Motor Inut (Watts)	58	68	74	140	180	180	
	FLA	0.26	0.31	0.34	0.64	0.82	0.82	
Coil Type:	Grooved Copper Tube - Hydrophilic Blue Fin							
Air Filter:	Cleanable Cartridge Type							
Electrical	Voltage-Phase-Frequency	220-240V / 1PH / 50Hz						
	Range (min-max)	198 min ~ 264 max						
	Cooling Rated Amps (min/max)	8 (2.3/10.4)	10.5 (4.5/12.0)	12.6 (4.5/15.1)	15.8 (5.5/16.1)	7.6 (2.6/8.8)	8.2 (3.0/9.4)	
	Heating Rated Amps (min/max)	7.5 (2.5/11.4)	10.0 (4.8/13.0)	12.6 (4.5/13.8)	15.5 (5.5/16.1)	7.3 (2.8/8.6)	8.1 (3.2/9.4)	
Controls	Wired (Std.) & Wireless (Opt.)							
Refrigerant Connections inches (mm)	See Outdoor Unit Data							
Drain Connection inches (mm)	1 (25)							
Body Dimensions inches (mm)	Depth	22 1/2 (570)	22 1/2 (570)	22 1/2 (570)	28 (710)	31 1/2 (800)	31 1/2 (800)	
	Height	8 1/4 (210)	8 1/4 (210)	10 5/8 (270)	10 5/8 (270)	11 7/8 (300)	11 7/8 (300)	
	Width	36 1/4 (920)	36 1/4 (920)	36 1/4 (920)	45 (1140)	47 1/4 (1200)	47 1/4 (1200)	
Net Weight Lbs (kgs)	47.3 (21.5)	48.4 (22)	57.2 (26)	81.4 (37)	96.8 (44)	96.8 (44)		

OUTDOOR UNIT								
MODEL NO.	ICHC	018J3A -LTG053	024J3A -LTG070	030J3A -LHG090	036J3A -LSG105	048J7A -LSG140	060J7A -LHG160	
Compressor	Type	Rotary						
	No of Fans	1						
	Motor Input (W)	33	33	54	85	85	200	
	Air Flow CFM (m3/h)	1765 (3000)	1765 (3000)	2120 (3600)	2120 (3600)	2945 (5000)	3295 (5600)	
Outdoor Fan	Noise Level (dbA)	57	53	57	56	57	58	
	Coil Type:	Grooved Copper Tube - Hydrophilic Blue Fin						
	Electrical	Voltage-Phase-Frequency	220-240V / 1PH / 50Hz				380-415V / 3PH / 50Hz	
Range (min-max)		198 min ~ 264 max				342 min ~ 457 max		
Comp. Power Input (W)		2080	2340	2535	3125	4580	4740	
Minimum Circuit Amps (MCA)		14.0	19.2	21.4	21.5	19.0	21.0	
Maximum Fuse Amps (MOCP)		25	30	35	35	15	20	
Refrigerant Charge R410a (oz./kgs.)	35.2 / 1.0	59.8 / 1.7	66.9 / 1.9	72.2 / 2.05	104.9 / 2.98	98.6 / 2.8		
Refrigerant Connections inches (mm)	Type	Flare						
	Liquid	1/4 (6.35)	1/4 (6.35)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)	
Max Pipe Distance Ft.(m)	Suction	1/2 (12.70)	1/2 (12.70)	5/8 (15.88)	5/8 (15.88)	5/8 (15.88)	5/8 (15.88)	
	Height	49.2 (15)	49.2 (15)	49.2 (15)	49.2 (15)	100 (30)	100 (30)	
Unit Dimensions inches (mm)	Length	98.4 (30)	98.4 (30)	98.4 (30)	98.4 (30)	165 (50)	165 (50)	
	Depth	11 3/8 (288)	11 3/8 (288)	13 (330)	14 1/8 (360)	14 1/8 (360)	16 1/8 (410)	
	Height	30 3/4 (780)	30 3/4 (780)	33 1/4 (845)	35 7/8 (910)	35 7/8 (910)	39 3/4 (1010)	
Net Weight Lbs (kgs)	23 1/4 (590)	23 1/4 (590)	27 1/2 (699)	31 3/4 (805)	31 3/4 (805)	33 1/2 (850)		
		61.6 (28)	68.2 (31)	94.6 (43)	103.4 (47)	143 (65)	165 (75)	

IEMP SERIES

Medium ESP Ducted Fan Coil
Inverter Air Conditioner 50 Hz

Cooling Nominal: 18,000 - 60,000 BTU/h (5.3 -16.0 kW)
Heating Nominal: 18,000 - 60,500 BTU/h (5.3 -17.7 kW)



IEMP



ICHC018~036



ICHC048-060



Wired Controller



Wireless Controller

Notes:

- Nominal capacities are based on ARI standards 210/240-89, air entering the indoor coil operating at high fan speed for 220V-240V setting. Cooling: 80/67° F (27/19° C) DB/WB indoor & 95° F (35° C) outdoor ambient temperature.
- Ratings are based on indoor and outdoor connected by 25ft (7.5m) of tubing.
- Refrigerant metering device is installed at the indoor unit as standard.
- Flare fittings are provided for connecting indoor and outdoor units.
- Insulation of suction line only is required.
- Outdoor units are shipped with full operating charge.
- For details of model number nomenclature, please refer to publication OMGNM-1117.