

VRF ULTIMA

OMEGA VRF TECHNOLOGY

Engineered to elevate efficiency and comfort
..... to the next level!

BEWM SERIES HIGH WALL VRF Indoor Unit Inverter Heat Pump 60 Hz

Cooling Capacity Min~Max: 7,505~30,710 BTU/h (2.2~9.0 kW)
Heating Capacity Min~Max: 8,190~34,120 BTU/h (2.4~10.0 kW)

Product Features

- ✓ Built-in Electronic Expansion Valve.
- ✓ Whisper Quiet Design.
- ✓ Auto Restart.
- ✓ Washable Filter.
- ✓ Self-Diagnostics Function.
- ✓ Factory Tested.
- ✓ Auto Swing (Vertical).
- ✓ Easy Installation & Maintenance

Indoor Unit Features

- ✓ Wireless LCD Remote Control (Standard).
- ✓ Wired LCD Remote Control (Optional).
- ✓ Deluxe Wired Controller with Weekly Timer (Optional).
- ✓ Centralized Controller (Optional).
- ✓ Remote Monitoring Software (Optional).
- ✓ Anti-Freezing Protection.
- ✓ Fan Motor Overload Protection.
- ✓ Temperature Sensor Malfunction.
- ✓ Cold Air Prevention Design (Heating Mode).



OMEGA



OTEC
AIR CONDITIONING

A Product of
OMEGA
Environmental
Technologies LLC.

ISO 14001 ISO 9001

VRF ULTIMA

OMEGA VRF TECHNOLOGY

Engineered to elevate efficiency and comfort
..... to the next level!

BEWM SERIES HIGH WALL VRF Indoor Unit Inverter Heat Pump 60 Hz

Cooling Capacity Min~Max: 7,505~30,710 BTU/h (2.2~9.0 kW)

Heating Capacity Min~Max: 8,190~34,120 BTU/h (2.4~10.0 kW)

HIGH WALL VRF Indoor Unit

MODEL NO.	BEWM	008Q	010Q	012Q	015Q	019Q	024Q	027Q	032Q	
		2A-DWV022	2A-DWV028	2A-DWV036	2A-DWV045	2A-DWV056	2A-DWV071	2A-DWV080	2A-DWV090	
Cooling Capacity	BTU/h (kW)	7,505 (2.2)	9,555 (2.8)	12,285 (3.6)	15,355 (4.5)	19,110 (5.6)	24,225 (7.1)	27,295 (8.0)	30,710 (9.0)	
Heating Capacity	BTU/h (kW)	8,190 (2.4)	10,920 (3.2)	13,650 (4.0)	17,060 (5.0)	21,495 (6.3)	27,295 (8.0)	30,710 (9.0)	34,120 (10.0)	
Refrigerant Control	Electronic Expansion Valve @ Indoor Unit									
Coil Type	Grooved Cooper Tubes - Hydrophilic Aluminum Fin									
Electrical	Voltage-Phase	208-230 / 1Ph								
	Frequency	60 Hz								
	FLA	0.20	0.20	0.20	0.30	0.30	0.40	0.40	0.40	
	Input (W)	29	29	31	45	54	77	77	90	
Air Filter	Cleanable Cartridge Type									
Fan	Type	Cross-Flow Fan								
	Speed	7-Speed								
	Qty	1	1	1	1	1	1	1	1	
	Air Flow CFM (m³/hr) (Hi)	260 (446)	270 (457)	265 (447)	380 (648)	470 (798)	730 (1240)	735 (1248)	840 (1427)	
	Noise Level Hi (db)	34	33	36	37	42	48	48	52	
Refrigerant Connections inches (mm)	Type	Branch Header								
	Liquid	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	1/4 (6.35)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)	
	Suction	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	1/2 (12.7)	5/8 (15.9)	5/8 (15.9)	5/8 (15.9)	5/8 (15.9)	
Drain Connections inches (mm)	5/8 (16)									
Dimensions inches (mm)	Height	11 (280)	11 (280)	11 (280)	12 1/2 (315)	12 1/2 (315)	13 1/2 (343)	13 1/2 (343)	13 1/2 (343)	
	Width	32 7/8 (835)	32 7/8 (835)	32 7/8 (835)	39 (990)	39 (990)	47 (1194)	47 (1194)	47 (1194)	
	Depth	8 (203)	8 (203)	8 (203)	8 3/4 (223)	8 3/4 (223)	10 3/8 (262)	10 3/8 (262)	10 3/8 (262)	
Net Weight Lbs (kgs)	18.7 (8.5)		18.7 (8.5)		21.4 (9.7)		30.4 (13.8)		30.4 (13.8)	



Wireless Controller
VAEWD-D001 (Optional)



Wireless Controller
VAEWR-D001 (Standard)



Wired Controller
VAECR-D001 (Standard)



Deluxe Wired Controller
VAECD-D001 (Optional)



Centralized Controller
VAECR-D064T (Optional)

- Notes:**
- Nominal capacities are based on ARI standards 210/240-89, air entering the indoor coil operating at high fan speed for 220V-240V setting. Cooling: 80/67° F (27/19° C) DB/WB indoor & 95° F (35° C) outdoor ambient temperature.
 - Refrigerant metering device is installed at the indoor unit as standard.

- Flare fittings are provided for connecting indoor and outdoor units.
- Insulation of both liquid and suction line is required (Heat Pump Mode).
- For details of model number nomenclature, please refer to publication OMGNM-0721.

OMEGA
ENVIRONMENTAL
TECHNOLOGIES LLC.
17702 Mitchell North, #101
Irvine, CA 92614, USA
Tel: 714 796 2830
Fax: 714 966 1649
info@omegainverter.com
www.omegainverter.com



ISO 14001 ISO 9001

OTEC
AIR CONDITIONING
Showroom & Technology Center
11380 Interchange Circle North
Miramar, FL 33025, USA
Tel: 305 731 2140, 888 840 7550
Fax: 954 212 8280
info@otecus.com
www.otecus.com