

OMEGA

TECHNOLOGY

Engineered to elevate efficiency and comfort
..... to the next level!!



IEUA

IEUA SERIES

16 SEER - Air Handler

50 & 60 Hz Split Cooling & Heating System

Cooling Nominal: 18,000-55,000 Btuh (5.3 - 16.0kW)

Heating Nominal: 19,000-55,000 Btuh (5.6 - 16.0kW)



ICHE

Product Features

- ✓ Up to 16 SEER Cooling
- ✓ Cooling and Heating System
- ✓ Auto Restart.
- ✓ Self-Diagnosis.
- ✓ R410A Refrigerant.
- ✓ Ideal for Small Commercial & Industrial Applications.

Outdoor Unit Features

- ✓ Designed for Cooling @ 46C °/115F ° ambient.
- ✓ Super Quiet Operation.
- ✓ Copper Tubes / AL Fins Condenser.
- ✓ Twin Rotary Inverter Compressor
- ✓ 18K,24K,48K,60K are using Mitsubishi Compressor
- ✓ 36K is using GMCC Compressor
- ✓ Compressor Overload Protection.
- ✓ Electronic Expansion Valve
- ✓ Fixed Orifice
- ✓ Sensata Pressure Sensor
- ✓ Match-Well Pressure Switch
- ✓ Intelligent Proportional Integral Control Logic

Indoor Unit Features

- ✓ R410A Environmental Refrigerant
- ✓ Galvanized Steel Cabinet
- ✓ Primary and Secondary Drainage Design
- ✓ Durable non Corrosive Plastic Drain Pans
- ✓ Piston Expansion Device
- ✓ Enhanced Aluminum Fins with Copper Tubing Coil
- ✓ Different Selections of Air Flow
- ✓ Φ 10.8" Blower with Powerful Fan
- ✓ Multi-Positions Installation
- ✓ Detachable Air Filter for Cleaning or Renewal
- ✓ Wired Controller (Std.)
- ✓ Remote Controller (Opt.)
- ✓ 24V Thermostat (Opt.)

OMEGA



OTEC
AIR CONDITIONING

A Product of
OMEGA
Environmental
Technologies LLC.

ISO 14001 ISO 9001

OMEGA

Engineered to elevate efficiency and comfort...
..... to the next level!

IEUA SERIES

16 SEER - Air Handler

50 & 60 Hz Split Cooling & Heating System
Cooling Nominal: 18,000-55,000 Btuh (5.3 - 16.0kW)
Heating Nominal: 19,000-55,000 Btuh (5.6 - 16.0kW)



IEUA



ICHE

Notes:

- Nominal capacities are based on ARI standards 210/240-89, air entering the indoor coil operating at high fan speed for 220V-240V setting. Cooling: 80/67° F (27/19° C) DB/WB indoor & 95° F (35° C) outdoor ambient temperature.
- Ratings are based on indoor and outdoor connected by 25ft (7.5m) of tubing.
- Refrigerant metering device is installed at the indoor unit as standard.
- Sweat fittings are provided for connecting indoor and outdoor units.
- Insulation of suction line only is required.
- Outdoor units are shipped with full operating charge.
- For details of model number nomenclature, please refer to publication OGMNM-1117.

INDOOR UNIT

MODEL NO.	IEUA	618K 2A-GNG053	624K 2A-GNG071	636K 2A-GNG105	648K 2A-GNG140	660K 2A-GNG160
Cooling Capacity Btuh (kW)	Nominal	18,000 (5.3)	24,000 (7.1)	36,000 (10.5)	48,000 (14.0)	60,000 (17.6)
Heating Capacity Btuh (kW)	Nominal	19,000 (5.6)	24,000 (7.1)	35,000 (10.3)	50,000 (14.7)	55,000 (16.1)
Efficiency - SEER	Btuh/W	16.0 (5.9)				
Refrigerant Control		Piston @ Indoor Unit				
Fan	Type	Centrifugal				
	Speed	2	2	3	3	3
	Air Flow CFM (m ³ /hr) - Hi	835 (1420)	835 (1420)	1235 (2100)	1676 (2850)	1676 (2850)
	Noise Level (dba) - Hi	57	57	57	58	58
	Static Pressure (Pa)	25	25	37	50	50
	Pressure Range (Pa)	0~100	0~100	0~160	0~200	0~200
	Motor Input (Watts)	225	225	305	545	545
Coil Type:		Grooved Copper Tubes - Hydrophilic Fin				
Air Filter:		Cleanable Cartridge Type				
Electrical	Voltage	208~230V-1PH-60Hz & 50Hz				
	Range	min 187 - max 253				
	FLA	1.0	1.0	1.3	2.4	2.4
Controls:		Wired Controller (Std.) - Remote Controller (Opt.) - 24V Thermostat (Opt.)				
Refrigerant Connections inches (mm)	Type	R410A				
	Liquid	1/2 (12.7)	1/2 (12.7)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)
Suction	5/8 (15.88)	5/8 (15.88)	3/4 (19.05)	3/4 (19.05)	3/4 (19.05)	
	Drain Connection Inches (mm)	1 (25)				
Dimensions inches (mm)	Height	30 1/2 (774)	30 1/2 (774)	46 (1170)	52 7/8 (1340)	52 7/8 (1340)
	Width	18 (460)	18 (460)	20 (510)	22 (560)	22 (560)
	Depth	20 1/2 (520)	20 1/2 (520)	22 (560)	24 (610)	24 (610)
Net Weight	Lbs (Kgs)	81.4 (37)	81.4 (37)	132 (60)	171.6 (78)	171.6 (78)

OUTDOOR UNIT

MODEL NO.	ICHE	618K 2A-GMG053	624K 2A-GMG071	636K 2A-GMG105	648K 2A-GMG140	660K 2A-GMG160
Compressor	Type	DC/Twin-Rotary				
	Rated Load Amps (RLA)	4.4	6.7	8.5	14.8	14.8
Outdoor Fan	No of Fans	1	1	1	1	1
	Motor Input (W)	152	152	197	370	370
	Air Flow CFM (m ³ /hr) - Hi	1941 (3300)	1941 (3300)	2470 (4200)	3235 (5500)	3530 (6000)
	Noise Level (dba)	54	54	56	57	57
Coil Type:		Grooved Copper Tubes / AL Fins Condenser				
Electrical	Voltage	208/230V - 1Ph - 60Hz & 50Hz				
	Range (min-max)	min 187 - max 253				
	Cooling Pwr. Input Nom. (W)	1300	1960	1945	3960	3960
	Min. Circuit Amps (MCA)	6.5	9.4	11.9	20.9	20.9
Refrigerant Charge R410a (oz./kgs.)		63.4 / 1.8	70.4 / 2.0	105.6 / 3.0	116.2 / 3.3	126.7 / 3.6
Refrigerant Connections inches (mm)	Type	Cooling: EXV - Heating: EXV				
	Liquid	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)	3/8 (9.52)
Suction	5/8 (15.9)	5/8 (15.9)	3/4 (19.1)	3/4 (19.1)	3/4 (19.1)	
	Max Pipe Distance Ft.(m)	Height	32 (10)	32 (10)	32 (10)	32 (10)
Length	100 (30)	100 (30)	100 (30)	100 (30)	100 (30)	
	Height	27 5/8 (702)	27 5/8 (702)	32 (810)	34 3/8 (870)	34 3/8 (870)
Width	36 7/8 (935)	36 7/8 (935)	40 5/8 (1032)	43 3/8 (1100)	43 3/8 (1100)	
	Depth	15 1/8 (383)	15 1/8 (383)	17 1/2 (445)	20 7/8 (528)	20 7/8 (528)
Net Weight	Lbs (Kgs)	92.4 (42)	100.1 (45.5)	132 (60)	165 (75)	176 (80)



OMEGA
ENVIRONMENTAL
TECHNOLOGIES LLC.
17702 Mitchell North, #101
Irvine, CA 92614, USA
Tel: 714 796 2830
Fax: 714 966 1649
info@otecomega.com
www.otecomega.com



ISO 14001 ISO 9001

OTEC
AIR CONDITIONING
Showroom & Technology Center
11380 Interchange Circle North
Miramar, FL 33025 . USA
Tel: 305 731 2140, 888 840 7550
Fax: 954 212 8280
info@otecomega.com
www.otecomega.com